

Smart Tweezers™ comparison ST-5S-BT2 vs. ST-5S vs. ST-5C

DISCONTINUED

Feature	Smart Tweezers™ ST-5S-BT2	Smart Tweezers™ ST-5S	Smart Tweezers™ ST-5C
Automatic Component Recognition	✓	✓	✓
L,C,R Measuring Modes	✓	✓	✓
ESR Measuring Mode	✓	✓	✓
Z Measuring Mode	✓	✓	
Diode Testing	✓	✓	
DCR Measuring Mode	✓	✓	
Component Sorting	✓	✓	
Manual Test Frequency Override	✓	✓	✓
Variable Test Signal Level	✓ (0.41, 0.91 VRMS)	✓ (0.41, 0.91 VRMS)	(0.5 VRMS)
Automatic Offset Substraction	✓	✓	
Individual Calibration Certificate	✓	✓	
High-Visibility OLED Display	✓	✓	✓
Typical Accuracy: Resistance	0.2%	0.2%	0.5%
Typical Accuracy: Capacitance	0.5%	0.5%	1.0%
Typical Accuracy: Inductance	0.5%	0.5%	1.0%
Gold-plated Test Leads	✓ (Swiss-Made)	✓ (Swiss-Made)	✓
Calibration - calibration certificate	✓	✓	
Bluetooth™ Connectivity	✓		