

ERGO-TEK LINE CUTTERS

CUTTER SIZES

	MICRO	SMALL	LARGE	EXTRA-LARGE
	513x series	514x / 534x / 544x / 554x series	515x / 535x / 555x series	516x series
Width A (mm)	8	10	12.5	16

CUTTER SHAPES

51xx series	53xx series	54xx series	55xx series	52xx series
Oval Head	Tapered Head	Oval & Relieved H.	Tapered & Relieved H.	Oblique Head
52xx series				
Special Head				

CUTTING BLADES & WIRE DEFINITION

			Wire definition <ul style="list-style-type: none"> • SOFT wire, copper, aluminium, tensile strength 250 MPa • MEDIUM-HARD wire, stainless steel wire, material 1.4301, tensile strength 800 MPa • HARD wire, stainless steel wire, material 1.4301, tensile strength 1800 MPa
SEMI-FLUSH	FLUSH	FULL-FLUSH	
xxx0 series	xxx1 series	xxx2 series	

HANDLE OPTIONS



COMPARISON



LEAD CATCHER



Wire Lead Catcher fits Oval, Tapered and Tapered & Relieved cutters with 10 mm box or 12,5 mm box.

Easily snapped in place without disassembling the tool.

To prevent wire from falling on work surface.